

PowerCrate-CE-5 PowerCrate-CE-15

昆宇电源
COSPOWERS

低压壁挂式储能电池



- 1 外观设计极其简洁，外观优雅，防护等级为IP40
- 2 支持多个电池模块并联，最多可达8个模块
- 3 安装和维护方便，可定制设计以满足不同客户的需求
- 4 具有多重保护和报警系统，安全可靠

参数/型号		CE-5	CE-15
电池参数	额定电压	51.2V	
	电压范围	45~57.6V	44.8~57.6V
	电量	5120Wh	14340Wh
	最大充放电电流	0.5C/1C	
	电池类型	磷酸铁锂	
工作条件	工作温度范围	0~45°C	
	存储温度范围	-15~60°C	-15~30°C
	湿度	5~95%	
	冷却方式	自然冷却	
	重量	53Kg	112Kg
	尺寸(W*D*H)	430*186*600mm	413*233*825mm
	安装方式	壁挂式	落地移动式
	通讯方式	CAN/RS485	
其他参数	匹配逆变器	派能、古瑞瓦特、硕日、固德威、锦浪、鹏城、日月源、Victron、索瑞德、施耐德、SMA、美世乐、拓宝、STUDER	派能、古瑞瓦特、硕日、固德威、鹏城、首航、日月元、Victron、索瑞德、施耐德、SMA、美世乐、拓宝、STUDER
	认证	IEC62619、CE-EMC、FCC、UL1973、UL9540A	



深圳昆宇电源科技有限公司

网址:WWW.COSPOWERS.COM

地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话:0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

PowerCrate-CE-5 PowerCrate-CE-15

LOW VOLTAGE WALL HANGING TYPE-ENERGY STORAGE BATTERY



- 1 Extremely simple design in appearance, elegant appearance, IP40
- 2 It supports multiple battery modules in parallel, up to 8 modules
- 3 Multiple protection and alarm system, safe and reliable
- 4 Easy installation and maintenance, customized design to meet the requirements of different customers

Parameters/ Model		CE-5	CE-15
Battery Parameters	Rated voltage	51.2V	
	Voltage range	45~57.6V	44.8~57.6V
	Energy	5120Wh	14340Wh
	Max discharge rate	0.5C/1C	
	Type of battery	LFP	
Operating condition	Operating temperature range	0~45°C	
	Storage temperature range	-15~60°C	-15~30°C
	Humidity	5~95%	
	Dissipation method	Natural cooling	
	Weight	53Kg	112Kg
	Size (W*D*H)	430*186*600mm	413*233*825mm
	Installation method	Wall-mounted	Portable floor-standing
	Communication method	CAN/RS485	
Others	Matched inverter	Pylontech, Growatt, Shorun, Goodwe, Jinlang, Pengcheng, RYR, Victron, Sorou, Schneider, SMA, MSL, Topower, STUDER	Pylontech, Growatt, Shorun, GoodWe, Pengcheng, Maiden Voyage, RYR, Victron, Sorou, Schneider, SMA, MSL, Topower, STUDER
	Certification	IEC62619, CE-EMC, FCC, UL1973, UL9540A	



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.